



In-Plant Trainings

Virtual Platform

Session 3 – Controls



Homework Questions

- What's the compression ratio of the single stage compressor below?
 - 13.5 psia inlet pressure
 - 113.5 discharge pressure
- Is discharge pressure psig or psia? If it is psig (assuming 1 atm=13.5 psi), $\frac{113.5_{gauge} + 13.5}{13.5a} = 9.4$
- If it is psia, $\frac{113.5}{13.5} = 8.4$

Homework Questions

- How can we find the compressor discharge pressure?
- I'd like to get feedback regarding dry air storage system in my facility. I have some doubts, that it is efficient. As for me, majority of air is going to consumers via two bypasses. If my thoughts are correct, do we need to keep all 6 dry tanks?
- How to calculate right size of dry (or wet tank)
- What material is best for compressed air lines – copper, steel, etc.?
- Pressure settings on Gardner Denver screw compressor –Robert Barrier
- Baseline unit for continuous operation, can these be on VFDs?

Homework Questions

- How do you know when you need additional wet or dry storage?
- How much moisture should an air dryer handle?
- Currently looking at installing another compressor in facility; question being which kind would be best for the space.
- Along with that; does it make sense to add a volume tank on the other side of the facility.
- What advantages do flow controllers have over the life of your compressor? Any situations when a controller would not help your overall system?

Homework Questions

- With the compressors in our mill, 2x centrifugal and 2x rotary screw, what would be the best operating strategy you would recommend? Run two centrifugal and trim with the rotary screw load/unloading? I can't seem to make the required ~7,000 CFM with the two centrifugals.
- How can I accurately measure the flow rate coming off the centrifugal compressors when there is less than 10 feet straight run of pipe after the compressor?
- what would be a good Kw/100CFM to aim for?
- During months with higher humidity, we have to leave the blowdown valves cracked open in order to keep the compressors from accumulating significant amounts of condensate. How could we reduce the amount of condensation without wasting air.

Homework Questions

- What are some determining factors on what works best to transport the air from the Air Compressor System to the End Users? For example, what type of piping is ideal?

Homework Questions


Name: Matt Kanuch

Company: Bendix

2. List your questions about the compressors in your facilities.

We have two rotary screw compressors, A VSD and a LOAD/UNLOAD. If our facility can be run off one 80-90% of the time, which type would you use as the lead compressor?


Load/No-load Control Curve



- This graph shows the effect of receiver size on the part load power of a lubricant injected rotary screw compressor with load/unload controls


Performance Curves

Various Compressor Control Performance Curves



Quick Review on Flowmeters

Types of Meters - Comparisons




	Thermal	Vortex	DP – Orifice plate	DP – Insertion	Coriolis	Turbine/ rotary displacement	Clamp on ultrasonic
Mass flow	Yes	Optional	Optional	Optional	Yes	Optional	Optional
Meter run	20D	15D	15D	20D	0D	10D	20D
Pressure loss	Low	Medium/high	high	Low	Low	Low	Low
Dirty air	Fouling	OK	Clogging	Fouling/Clog	Internal fouling	Failure	OK
Wet Air	Spikes	OK, spikes	OK	OK, orientation	Yes, but affects reading	Failure	Spikes
Range	1:250	1:10	1:10	1:10	1:100	1:100	1:100
Accuracy	2%	2%	2%	2%	0.5 .. 1%	0.5...1 %	1%
Purchase price	\$	\$	\$	\$S	\$\$\$\$	\$\$	\$\$\$
Maintenance	Medium	Low	Medium	Medium	Low	High	Low

Orifice Plate Flow Meters

These meters are another carry over from fluid engineering.


They operate on the physics of a pressure drop being created as a medium flows through an orifice.

The problem with these meters is just that; they, themselves are a pressure drop.




Differential Pressure Technology

- Speed of air creates differential pressure signal over the positive and negative port.
- Low speeds do not generate a stable Dif. Pressure.



Differential Pressure Technology

- Unique sensitivity in the lower measuring range: Measures from as little as 2 m/s and thus covers the complete operating range of variable speed drive (VSD) compressors
- Particularly suitable for extremely high flow rates
- Flow, total consumption, temperature and pressure
- Measurement at high temperatures, max. temperature 180 °C
- Installation via 1/2" ball valve under pressure.



Min and Max Flow per Pipe Size

- DP flow meters have a min and max flow range. Below the minimum range the flow meter will read flaky or no flow, we call this the dead zone, 0 to 20 m/sec (0 to 65 ft/sec).
- In different pipe sizes this dead zone will have a different Q min, see the tables below.






Schedule 40 Standard Seamless Carbon Steel Pipe

Size (inch)	DN	ID (inch)	ID (mm)	Min flow (scfm)	Max flow (scfm)	Min flow (m ³ /hr)	Max flow (m ³ /hr)
2	50	2,1	52,5	92	917	156	1559
3	80	3,1	77,9	202	2021	343	3434
4	100	4,0	102,3	348	3481	591	5913
6	150	6,1	154,1	790	7899	1342	13420
8	200	8,0	202,7	1368	13678	2324	23238
10	250	10,2	259,1	2234	22341	3796	37957
12	300	11,9	303,2	3060	30604	5199	51994
16	400	15,0	381,0	4832	48316	8209	82087
20	500	18,8	477,8	7599	75994	12911	129110

Schedule 10 Standard Seamless Carbon Steel Pipe


ID (inch)	ID (mm)	Min flow (scfm)	Max flow (scfm)	Min flow (m ³ /hr)	Max flow (m ³ /hr)
2,2	54,8	100	999	170	1697
3,3	82,8	228	2282	388	3877
4,3	108,2	390	3897	662	6621
6,4	161,5	868	8678	1474	14743
8,3	211,6	1490	14897	2531	25309
10,4	264,7	2332	23316	3961	39612
12,4	314,7	3296	32965	5601	56006
15,6	396,8	5242	52420	8906	89058
19,6	496,9	8219	82191	13964	139638

Flow Meter Location

Picture	Description	Upstream length ²	Downstream length ²	Effect
	Single elbow	30 * D1	10 * D1	Distorted flow profile
	Complex feed-in situation (header)	40 * D1	10 * D1	Flow profile will be distorted
	Double elbow, multiple elbows following each other	40 * D1	10 * D1	Distorted profile + swirl
	Diameter change from small to large (gradual or instant)	40 * D1	5 * D1	Jet shaped flow
	Diameter change from large to small (gradual change, between 7 and 15 degrees)	10 * D1	5 * D1	Flattened flow profile

DP Insertion Flow Meters


- Insertion style Differential Pressure meter for saturated compressed air flow measurements.
- A differential pressure flow sensor measures bi-directional flow, pressure, temperature and total flow simultaneously.
- They are intended for use in high velocity applications where there is a continuous flow over a minimum value, such as compressor efficiency monitoring.



Compressor Controls


Compressor Control Types

- Start/Stop
- Load/Unload
- Modulating
- Variable Displacement
- Variable Speed



Inlet Valve

Inlet Throttling




AIR LEAKAGE


Female Rotor

Male Rotor

Stator




Capacity Control by Inlet Throttling




- Atmospheric pressure 14.7 psia
- Intake pressure 9.0 psia
- Discharge pressure 114.7
- Compression ratio: $114.7/9.0 = 12.7$ to 1
- End Result?? Increased internal leakage due to a higher compression ratio

Capacity Control by Inlet Throttling




- Varies capacity by throttling (restricting) the inlet flow
- Provides a relatively stable output pressure
- Energy hog... least efficient
- Every 10% reduction in capacity yields only a 3% reduction in power(BHP)
- At zero capacity, power remains at 70% of full load power

Inlet Valve Modulation



- The example shows a discharge pressure range of 100 - 110 psig.
- As discharge pressure rises from 100 to 110 psig, a proportional pressure regulator provides a control pressure from 0 - 30 psig, to progressively close the inlet valve.
- As the inlet valve closes, the absolute pressure at the inlet of the air end is reduced.

Inlet Valve Modulation




- This reduces the mass flow of air entering the air end in direct proportion to the absolute pressure.
- However, the reduced inlet pressure, with increasing discharge pressure, results in increasing pressure ratio.
- At 40% capacity the pressure ratio will be $124.7/5.88 = 21.21$.
- This is why there is not much reduction in the power requirement.


Variable Displacement

- Valves progressively opens ports connecting the compression chamber back to the compressor intake in response to rising discharge pressure. This allows some of the intake air to be returned to the compressor inlet before it gets compressed and uses power
- This progressive opening of by-pass ports has the effect of shortening the length of the rotors after the lobes seal without choking the intake and increasing the compression ratio


Variable Displacement



Variable Displacement




Variable Displacement



Variable Displacement


Original Version





— UP TO 55% TURN DOWN




Variable Displacement



Variable Displacement



Load/No-load Control Curve




- This graph shows the effect of receiver size on the part load power of a lubricant injected rotary screw compressor with load/unload controls


Load/Unload and Storage Size

- It is falsely assumed that a straight line, from full load bhp to unloaded bhp, represents the actual power requirement in this mode of operation.
- Sump blow down times will vary by machine size, but typically this takes in the range of 20 to 60 seconds to prevent foaming of the lubricant with the potential of excessive lubricant carry-over.
- In many cases, the system pressure will fall and the compressor will re-load before the fully unloaded power is realized.

Capacity Control by Load/No-Load




- During blow-off, the compressor is still running against significant back pressure and consuming a lot of power
- Bigger sump vessels lead to longer blow-off times and more energy consumption



Capacity Control by Load/No-Load


Active Power consumption evolution from L to NL



Variable Speed Compressors


- Efficient means of rotary compressor capacity control,
- Integrated variable frequency AC or
- Switched reluctance DC drives.
- Compressor discharge pressure can be held to within +/- 1
- In order to provide efficient VSD regulation over the complete range of the customer's air profile, the VSD operational flow from min to max, needs to be sized so it will always be in its turndown range.

Variable Speed



Performance Curves

Various Compressor Control Performance Curves



Variable Speed Compressors


- The most common VSD is the variable frequency drive, which converts 60 Hz alternating current to direct current and then reconverts it to the proper frequency required to turn the drive motor at the desired speed.
- The variable frequency drive is less efficient at full load compared to modulation controls because the electrical conversions usually consume an additional two to four percent more energy.

Variable Speed Compressors

- VSD (variable speed drive) and VFD (variable frequency drive) are used interchangeably
- VFD is only one of the VSD technologies available.


Variable Speed Compressors

- In order to provide efficient VSD regulation over the complete range of the customer's air profile, the range of the VSD from min to max needs to be sized greater than the load/no load machine




Variable Speed Compressors and Control Gap

This system can provide a steady operating pressure throughout the flow range of the system as long as the system is properly controlled with a master controller.




How do I know my flow patterns to size a VSD Correctly?


Flow Histogram
Mean=658.2, Standard Deviation=124.469, Skewness=-0.238556




How do I know my flow patterns to size a VSD Correctly?



How do I know my flow patterns to size a VSD Correctly?




How do I know my flow patterns to size a VSD Correctly?





Control Gap and Position

- In order to provide efficient VSD regulation over the complete range of the customer's air profile, the cfm of the VSD needs to be greater than the load/no load machine




Centrifugal Compressor Control


- Performance is affected by inlet conditions and cooling water temperature
- Characteristic curve is determined by impeller design
- Two conditions should be avoided:
 - Surge (flow reversal)
 - Choke (excessive flow vs. frame design)
- Inlet throttle valves modulate the compressor to reduced flow and power but are limited by surge condition
- Blow-off valves control capacity below throttling limit




Building the Profile



Centrifugal Compressor Control Common Terms




How do I know how to size Centrifugal to my flow Patterns?




- Plant has 8000 cfm peak demand, 5800 cfm average demand, and 3000 cfm minimum demand during weekends at operating pressure of 100 psig.
- Two 4000 cfm centrifugals with a 30% turndown to 2800 cfm

How do I know how to size Centrifugal to my flow Patterns?




- During peak demand of 8000 cfm, both compressors will run at full load.
- When the flow demand is reduced to the average demand of 5800 cfm, the two centrifugal compressors will close the inlet guide valve and run in its turndown range without exhausting any compressed air to atmosphere.

How do I know how to size Centrifugal to my flow Patterns?



- During the weekend, when the demand reaches to minimum flow of 3000 cfm, one centrifugal compressor will stop and only one compressor will run in its turndown range.
- With this combination, the centrifugal compressors will work most efficiently and save a plant significant energy.
- If flow drops below min flow of the centrifugal, a rotary screw can be added to assist with keeping the plant operating and allowing the centrifugal to stay out of blow down.

How do I know how to size Centrifugal to my flow Patterns?






Inlet Guide Vanes - Open



Inlet Guide Vanes - Closed




Inlet Guide Vanes



- This valve positioner consists of a common housing that contains a 4 – 20 mA current to pressure (I/P) transducer that controls the attached pilot valve operated air to actuator assembly.
- The positioner will output 0 to 65 psi (448 kPa) to the actuator from an air signal.
- The air signal provided by the positioner is proportional to the microcontroller 4 – 20 mA output.
- The actuator provides the power to drive the valve open or closed in proportion to the microprocessor output control signal.

Centrifugal Compressor Control


The relationship of flow and pressure for dynamic compressors is different from that of positive displacement machines.



Effects on dynamic compressor performance


- Inlet pressure
- Inlet air temperature
- Cooling water temperature

Centrifugal Performance




INLET TEMPERATURE CHANGE – EFFECT ON AIR OUTPUT

Capacity at 95°F inlet Temp



2,315 scfm, 497.75 HP, 24 psi rise to surge


Capacity at 119°F inlet Temp



2,103 scfm, 467.74 HP, 15 psi rise to surge


DISCHARGE PRESSURE CHANGE – EFFECT ON AIR OUTPUT

Capacity at 110 psig discharge pressure



2,103 scfm, 467.74 HP, 15 psi rise to surge


Capacity at 118 psig discharge pressure



2,030 scfm, 464.94 HP, 7 psi rise to surge


Inlet Pressure Effects On Dynamic Compressor Performance

Inlet pressure




Cooling Water Effects On Dynamic Compressor Performance

Cooling water temperature




Inlet Air Temperature Effects On Dynamic Compressor Performance


Inlet air temperature influence





Curve showing air compressor performance at a 34°F inlet, 60% RH, 77°F Coolant and 125 psig discharge pressure:





Curve showing air compressor horse power at a 34°F inlet, 60% RH, 77°F Coolant and 125 psig discharge pressure:



Curve showing air compressor performance at a 104°F inlet, 100% RH, 77°F Coolant and 125 psig discharge pressure:



Curve showing air compressor horsepower at a 104°F inlet, 100% RH, 77°F Coolant and 125 psig discharge pressure:




Multiple Compressor Control

- Holds a constant air pressure in the network within narrow limits.
- Easy to install.
- Connectable to all kinds of compressors.
- Optimisation of service intervals = lower service cost.
- Priority selection : old versus new machines.
- Delayed start : NEVER start two machines or more at the same time => high current peaks are avoided.
- Base load compressors can fill a net in advance to avoid load peaks.

Multiple Compressor Control

- Very simple user interface = minimum user training.
- Machines are used more efficiently.
- Energy reduction = immediately saves money.
- Full compressor & network status feed- back.
- Programmable pressure schedule.
- PC monitoring & analysing possibilities.


Cascade Compressor Control




- Base load as many compressors as possible.
- Traditional cascade control can be inefficient.

Master Controls

- Basic single set point control scheme



Master Control Basics



Cascaded Pressure Switches


Vs

Master

Pressure/Flow Controllers


- Primary function: Stabilize pressure regardless of demand
- Most compressor controls cause 3-10 psi swings
- Multiple compressors can compound the system pressure swings
- Pressure/flow controllers typically hold pressure to production within $\pm 1\%$ of set point
- The following graph is from a system with 9 compressors totaling over 6,000 hp – pressure is set at 79 psig

Pressure/Flow Controllers




- The compressor discharge pressure varies about 10 psi as the trim compressor loads and unloads to meet plant demand.
- The pressure to the plant is kept at a constant 79 psig.

Pressure/Flow Controllers




Pressure/Flow Controllers




Pressure/Flow Controllers

South Compressor Room psig comparisons




Pressure/Flow Controllers



Pressure/Flow Controllers




Pressure/Flow Controllers




- A typical block diagram of a pressure/flow controller in a compressed air system with one point of entry (single compressor room)

Pressure/Flow Controllers




Primary Storage




How does Volume Help

- A paint area in a body shop has a 5 HP compressor mounted on an 80-gallon air receiver. This receiver is pumped up to 175 psig. The air flow to the buffer which uses 18 SCFM at 90 PSIG, is regulated to 90 PSIG outflow from the regulator.
- The compressor delivers 12-13 SCFM at 90 psig but yet it runs the 18 SCFM sander just fine.
- How can this work???
- The buffer uses more volume(scfm) than the compressor can deliver !!
- If there were no regulation and receiver, you can be sure that the compressor would not be able to run the tool



How does Volume Help



With no receiver, the painter must install a second 5 hp compressor and therefore use twice the energy as before

Controls Summary

- Create a control strategy:
 - ✓ Know how your controls work
 - ✓ Realize the pros and cons of different controls
 - ✓ Recognize how controls affect part load efficiency
 - ✓ Understand how storage affects the effectiveness of control strategies


Logtool, AirMaster+ and the MEASUR Tool

Why AIRMaster+?

- ~90% of energy input to compressor never reaches tools (waste heat, drying, etc.)
- Leaks +pressure drops remove air energy before reaching tools--sometimes >50%
- Poor or improperly adjusted controls leave several compressors operating a part load
- System assessments can be an arduous task using spreadsheets that must be modified for each job
- AIRMaster+ provides a systematic approach to assessing compressed air systems, analyzing collected data, and reporting results

What Can This Tool Help Me With?

There are two basic ways to reduce the energy consumption of a compressed air system: produce compressed air more efficiently; and consume less compressed air.




What Can This Tool Help Me With?

- Produce more efficiently
 - Improve Compressor Control
 - Type of Compressor Control
- Use less compressed air
 - Reduce System Pressure
 - Reduce Air Demand
 - How does compressed air support production?

Compressed Air Versus Other Energy Sources

- 1 hp air motor = 7-8 hp of electrical power
 - 30 scfm @ 90 psig is required by the air motor
 - 6 - 7 bhp at compressor shaft required for 30 scfm
 - 7 - 8 hp electrical power required for this
- Annual energy cost for a 1 hp air motor versus a 1 hp electric motor, 5-day per week, 2 shift operation, \$0.05/kWh
- \$ 1,164 vs. \$ 194



AIRMaster+ Features

- AIRMaster+ is a Windows-based software tool used to analyze industrial compressed air systems:
- Simulates existing and modified compressed air system operation
- Models part load system operation
- Assigns electrical utility energy schedules
- Enters 24-hour metered airflow or power data
- Is not a substitute for an experienced auditor!

Energy Efficiency Measures

1. Reduce Air Leaks
2. Improve End Use Efficiency
3. Reduce System Air Pressure
4. Use Unloading Controls
5. Adjust Cascading Set Points
6. Use Automatic Sequencer
7. Reduce Run Time
8. Add Primary Receiver Volume

Why LogTool?

- LogTool is a public domain tool developed by SBW Consulting with support from the Compressed Air Challenge™.
- It is designed to assist in the analysis of compressed air system performance measurements.
- It is a companion tool for Airmaster+ available from the US DOE and CAC.


LogTool is Designed To:

- Import data which is exported from different types of data loggers.
- Select logger data channels and modify their properties.
 - e.g., name, type, units, etc.
- View data values for one or more logger channels.
- Display trend plots on one or two Y axis.
- Display scatter plots.
- Display daytype plots in the format that is needed for AIRMaster+

Enter LogTool Data Into AIRMaster

- Enter Utility and rate information
- Enter System information including Day Types
- Enter compressor Information
- Enter recorded data to establish the baseline
 - This data comes from LogTool
- Experiment with different EEM's

AIRMaster+ Main Menu



MEASUR Main Menu



Welcome to the most efficient way to manage and optimize your facilities' systems and equipment.

Create an assessment to model your system and find opportunities for efficiency or run calculations from one of our many property and equipment calculators.

Get started with one of the following options.

If you need help at any point along the way, click on a [User Manual](#) icon.



View Assessments



Equipment Calculators



Pump
Assessment



Compressed Air
Assessment



Process Heating
Assessment



Fan
Assessment



Steam
Assessment



Treasure
Hunt



Wastewater
Assessment




Motor
Inventory



Data
Exploration

U.S. DEPARTMENT OF
ENERGY | Energy Efficiency &
Renewable Energy

Box Plant Company Example



Baseline Info

- 200 hp baseloaded compressor rated 1014 acfm using modulated inlet control
- 250 hp trim compressor rated 1269 acfm using modulated inlet control operating at 40% output
- Production is 24/6 with Sundays off
- Average flow during Monday to Saturday is 1500 cfm
- Baseline energy is 2,587,516 kWh or \$174,657 using \$.0675/kWh
- Leakage is estimated to be about 600 cfm based on leak down test

Baseline Info

- Air Operated Diaphragm Pumps (AOD) are in use and can be replaced with electric driven pumps made to pump heavy viscous fluids such as glue
- 3-inch pipe is used in the compressor room to handle almost 1500 scfm of flow. This is borderline undersized and is creating additional pressure drop.
- Both compressors must run to support production. Neither one by itself can run production. There is no redundancy at this plant for compressed air.


Table 4.7 Loss of Air Pressure Due to Friction

Cu ft Free Air Per Min	Equivalent Cu ft Compressed Air Per Min	Nominal Diameter, In.												
		1/2	3/4	1	1 1/4	1 1/2	2	3	4	6	8	10	12	
10	1.28	6.50	.99	0.28										
20	2.56	25.9	3.90	1.11	0.25	0.11								
30	3.84	58.5	9.01	2.51	0.57	0.26								
40	5.12	16.0	4.45	1.03	0.46								
50	6.41	25.1	9.96	1.61	0.71	0.19							
60	7.68	36.2	10.0	2.32	1.02	0.28							
70	8.96	49.3	13.7	3.16	1.40	0.37							
80	10.24	64.5	17.8	4.14	1.83	0.49							
90	11.52	82.8	22.6	5.23	2.32	0.62							
100	12.81	27.9	6.47	2.86	0.77							
125	15.82	48.6	10.2	4.49	1.19							
150	19.23	62.8	14.6	6.43	1.72	0.21						
175	22.40	19.8	8.72	2.36	0.28						
200	25.62	25.9	11.4	3.06	0.37						
250	31.64	40.4	17.9	4.78	0.58						
300	38.44	58.2	25.8	6.85	0.84	0.20					
350	44.80	35.1	9.36	1.14	0.27					
400	51.24	45.8	12.1	1.50	0.35					
450	57.65	58.0	15.4	1.89	0.46					
500	63.28	71.6	19.2	2.34	0.55					
600	76.88	27.6	3.36	0.79					
700	89.60	37.7	4.55	1.09					
800	102.5	49.0	5.89	1.42					
900	115.3	62.3	7.6	1.80					
1 000	128.1	76.9	9.3	2.21					
1,500	192.3	21.0	4.9	0.57				
2,000	256.2	37.4	8.8	0.99	0.24			
2,500	316.4	58.4	13.8	1.57	0.37			


LogTool Trend Plot

Interval data [3 seconds] for System [Not Assigned] and Periods [Not Assigned]
1/11/2018 12:02:25 PM to 1/23/2018 6:33:51 PM

Pressure and Power Profile




LogTool Trend Plot




Bleed Down Test Calculation

Cfm Leakage =	[V x (P1 - P2) x 1.25]/(T x 14.7)						
Where	V=	453.9 Cu ft					
	P1=	118.66	Psig				
	P2 =	59.33	Psig				
	T =	3.50	Minute				
Cfm Leakage =	654.34						
% Leakage =	Measured cfm leakage/total cfm output of plant compressors						
% Leakage =	32.3%	Assuming 4cfm/hp and total HP of 450					


LogTool Trend Plot



LogTool Scatter Plot



LogTool Scatter Plot



Logger File Type

Help

Select Logger Data Files

- Force Pocket Logger Software
- HOBQware for Windows
- FLUKE Hydra Logger
- DP 3000 Configuration Software
- SULLAIR LogAir Software
- Ranger Pronto For Windows
- Wonderware ActiveFactory
- Unknown Logger Software

Logger Data Files

Import	File Name	Start	End	Interval (sec.)	File Status

Channels in Files Checked for Import

Import	File Name	Logger ID	Logger Name	Ch #	Name	Type	Units	Period	System

Import Checked Channels

Check All Channels

Uncheck All Channels

Logger Channels Imported to this MDB File

Delete	Name	Type	Units	Period	System	Start	End	Interval (sec.)
<input type="checkbox"/>	Wet Tank	Pressure	psig	Not Assigned	Not Assigned	1/11/2018 11:46:51	1/23/2018 14:40:00	3
<input type="checkbox"/>	Dry Tank	Pressure	psig	Not Assigned	Not Assigned	1/11/2018 11:43:14	1/23/2018 14:36:23	3
<input type="checkbox"/>	40 inch pre feed	Pressure	psig	Not Assigned	Not Assigned	1/11/2018 12:12:03	1/23/2018 15:05:12	3
<input type="checkbox"/>	40 inch main header	Pressure	psig	Not Assigned	Not Assigned	1/11/2018 12:15:25	1/23/2018 15:08:34	3
<input type="checkbox"/>	Exit Conveyor Push	Pressure	psig	Not Assigned	Not Assigned	1/11/2018 12:22:10	1/23/2018 15:15:19	3
<input type="checkbox"/>	Waste Water	Pressure	psig	Not Assigned	Not Assigned	1/11/2018 12:05:48	1/23/2018 14:58:57	3
<input type="checkbox"/>	200 QNw	Power	kW	Not Assigned	Not Assigned	1/11/2018 11:35:38	1/23/2018 14:29:59	3
<input type="checkbox"/>	250 QNw	Power	kW	Not Assigned	Not Assigned	1/11/2018 11:31:38	1/23/2018 14:24:47	3

Delete Checked Channels

LogTool Main Menu

LogTool v2

File Tools Help

Open/Create Database file to store logger data

File: IP LogTool.mdb

Folder: D:\WEEC 2018\International Paper Company

Logger Data in: IP LogTool.mdb


View	Trend		Scatter		DayType	Name	Type	Units	Period	System	Start	End	Interval (sec.)
	Y1	Y2	X	Y	Include								
Data	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Wet Tank	Pressure	psig	Not Assigned	Not Assigned	1/11/2018 11:46:51	1/23/2018 14:40:00	3
Data	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Dry Tank	Pressure	psig	Not Assigned	Not Assigned	1/11/2018 11:43:14	1/23/2018 14:36:23	3
Data	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	40 inch pre feed	Pressure	psig	Not Assigned	Not Assigned	1/11/2018 12:12:03	1/23/2018 15:05:12	3
Data	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	40 inch main head	Pressure	psig	Not Assigned	Not Assigned	1/11/2018 12:15:25	1/23/2018 15:08:34	3
Data	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Exit Conveyor Pust	Pressure	psig	Not Assigned	Not Assigned	1/11/2018 12:22:10	1/23/2018 15:15:19	3
Data	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Waste Water	Pressure	psig	Not Assigned	Not Assigned	1/11/2018 12:05:48	1/23/2018 14:58:57	3
Data	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	200 QNW	Power	kW	Not Assigned	Not Assigned	1/11/2018 11:35:38	1/23/2018 14:29:59	3
Data	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	250 QNW	Power	kW	Not Assigned	Not Assigned	1/11/2018 11:31:38	1/23/2018 14:24:47	3

Uncheck

Enter LogTool Data Into AIRMaster

DayType Analysis
✕

System: Not Assigned, Period: Not Assigned



Right click on data points to select day type. Left click to highlight the trace.

Click a date to highlight profile in graph.

Date	Day	Day Type
Jan-11-2018	Thu	Excluded Days
Jan-12-2018	Fri	Production
Jan-13-2018	Sat	Production
Jan-14-2018	Sun	Sunday
Jan-15-2018	Mon	Monday
Jan-16-2018	Tue	Production
Jan-17-2018	Wed	Production
Jan-18-2018	Thu	Production
Jan-19-2018	Fri	Production
Jan-20-2018	Sat	Production
Jan-21-2018	Sun	Excluded Days
Jan-22-2018	Mon	Excluded Days
Jan-23-2018	Tue	Excluded Days

Plot Day Type ...
Remove Day Type...


All Days

Caution: Day profiles can be similar even though different equipment, e.g., compressors, is operating. Use Trend Plots to examine the details of equipment operation before determining whether days should be assigned to the same daytype.


Create System DayType Profiles
Copy Plot to Clipboard
Copy Profiles to Clipboard
Help

System DayType Profiles									
	DayTypeName	ChannelName	Hr_01	Hr_02	Hr_03	Hr_04	Hr_05	Hr_06	Hr_07
▶	Monday	200 QNW	0.00	0.00	0.00	0.00	84.55	175.88	177.13
	Monday	250 QNW	0.00	0.00	0.00	0.00	83.80	164.18	163.56
	Production	200 QNW	178.12	178.25	177.86	177.11	177.67	178.09	177.97
	Production	250 QNW	166.54	166.81	167.49	168.31	168.50	168.50	168.40
	Sunday	200 QNW	181.76	180.51	179.20	176.98	154.17	0.00	0.00
	Sunday	250 QNW	165.56	163.78	162.43	161.83	143.08	0.00	0.00


DayType Profiles



DayType Profiles



DayType Profiles



Enter LogTool Data Into AIRMaster

- Enter Utility and rate information
- Enter System information including Day Types
- Enter compressor Information
- Enter recorded data to establish the baseline
 - This data comes from LogTool
- Experiment with different EEM's

Utility and Rate Information

Utility

File Calculators Help

Close

Utility **SRP** Rate Schedules

Utility Data

Utility name SRP

Utility code

Address 1

Address 2

City

State/Zip

Contact

Phone () -

Utility Rate Schedules

File Calculators Help

Close

Utility SRP

Rate Schedule **E61**

Rate Schedule

Description E61

	Season 1	Season 2
Start Month/Day	04/01	10/01
Demand rate (\$/kW-mo)	0.00	0.00
Energy Rate (\$/kWh)		
Block 1	0.06750	0.06750
Block 2	0.00000	0.00000
Block 3	0.00000	0.00000

System Information

The screenshot shows a software window titled "System" with a menu bar (File, Calculators, Help) and a toolbar. Below the toolbar are two dropdown menus: "Facility" and "System" (set to "Production"). The main area has four tabs: "System Data" (selected), "Sequencer Data", "Daytypes", and "End Uses".

System Data Tab:

- System name:
- Contact:
- Phone: () -
- Sequencer used:
- Sequencer type: Cascade pressures, Target pressure
- Calculated airflow capacity (sum of compressors), acfm:
- Nominal system pressure, psig:
- System elevation, feet:
- Air storage capacity (receivers + distribution pipe), ft3 *:
-

* Air storage capacity refers to unregulated (primary) storage. This field is required to run Add Receiver Volume efficiency measure.

System Information Day Types

System

File Calculators Help

Facility System Production

System Data Sequencer Data **Daytypes** End Uses


Daytype Description	Operating Days - Season 1	Operating Days - Season 2
Monday	52	0
Week Day	261	0
Sunday	52	0

Season 1 demand months

Season 2 demand months

Total annual days

Total down days



Compressor Information

Compressor Catalog

Search Select Clear Add Copy [Print] [Help] Cancel

Search Criteria

Compressor type: Single stage lubricant-injected rotary screw

Control type: Inlet modulation without unloading

Manufacturer: -All-

Motor power rating, hp - kW: -All- User-created only

Desired capacity, acfm: [] +/- [] %

Desired full load pressure, psig: [] +/- [] %

Search results - 13
Scroll right for more

Compressor Details

Compressor Type	Manufacturer	Model	Motor Rating, hp	Control Type
Single stage lubricant-injected rotary screw	<Generic>	200 hp/150 kW	200	Inlet modulation without un
Single stage lubricant-injected rotary screw	<Generic>	200 hp/150 kW	200	Inlet modulation without un
Single stage lubricant-injected rotary screw	<Generic>	200 hp/150 kW	200	Inlet modulation without un
Single stage lubricant-injected rotary screw	<Generic>	200 hp/150 kW	200	Inlet modulation without un
Single stage lubricant-injected rotary screw	<Generic>	200 hp/150 kW	200	Inlet modulation without un
Single stage lubricant-injected rotary screw	<Generic>	200 hp/150 kW	200	Inlet modulation without un
Single stage lubricant-injected rotary screw	<Generic>	200 hp/150 kW	200	Inlet modulation without un
Single stage lubricant-injected rotary screw	<Generic>	200 hp/150 kW	200	Inlet modulation without un
Single stage lubricant-injected rotary screw	<Generic>	250 hp/185 kW	250	Inlet modulation without un
Single stage lubricant-injected rotary screw	<Generic>	250 hp/185 kW	250	Inlet modulation without un

Compressor Information

Compressor Inventory
✕

File Calculators Help

📄 ✎ 💾 🗑️ 📄 ?
Copy Compressor
Query Inventory
Copy To Catalog
Close

Facility International Paper ▾

System Production ▾

Compressor 200 hp QNW ▾

200 hp, Single Stage Rotary Screw, 1005 acfm

User-assigned ID 200 hp QNW

Description 200 hp QNW

Compressor discharge control range 110.0 - 120.0 psig

Sequencer used

Manufacturer Compressor Details...

Nameplate
Controls
Performance
Totals (from Profile module)

Inlet Conditions

Avg. temperature, °F 85

Atmos. pressure, psia 14.2

Performance Points	Discharge Pressure	Airflow	Power
[actual, not rated]	psig	Dflt? acfm	Dflt? kW
Full load (cut-in)	110.0	<input checked="" type="checkbox"/> 1005	<input type="checkbox"/> 175.0 ...
Max full flow (mod begins)	110.0	<input checked="" type="checkbox"/> 1005	<input checked="" type="checkbox"/> 175.0 ...
Unload point (cut-out)	120.0	<input type="checkbox"/> 406	<input checked="" type="checkbox"/> 138.5 ...
No load (unloaded)	15.0	<input checked="" type="checkbox"/> 0	<input checked="" type="checkbox"/> 35.8 ...


Unloading Blowdown Time

For lubricant-injected rotary screws, sec. 40

Pressures are referenced from the compressor discharge.

Performance Profile...

Compressor Information



Enter LogTool Data Into AIRMaster

System	Type	Period	DayTypeNa	ChannelName	Hr_01	Hr_02	Hr_03	Hr_04	Hr_05	Hr_06	Hr_07	Hr_08	Hr_09	Hr_10	Hr_11	Hr_12	Hr_13	Hr_14	Hr_15	Hr_16	Hr_17	Hr_18	Hr_19	Hr_20	Hr_21	Hr_22	Hr_23	Hr_24
Not Assigned	Power	Not Assigned	Monday	200 QNW	0.0	0.0	0.0	0.0	84.6	175.9	177.1	181.6	182.2	180.8	177.2	177.7	177.0	178.6	178.7	178.7	176.9	177.0	178.2	177.2	178.7	179.6	180.1	179.3
Not Assigned	Power	Not Assigned	Monday	250 QNW	0.0	0.0	0.0	0.0	83.8	164.2	163.6	164.5	165.0	166.7	171.6	169.9	168.1	164.9	163.3	162.5	163.6	164.8	165.6	167.1	167.1	167.0	166.2	166.9
Not Assigned	Power	Not Assigned	Production	200 QNW	178.1	178.3	177.9	177.1	177.7	178.1	178.0	177.9	177.7	178.1	177.3	177.2	177.2	168.0	174.9	175.7	175.7	175.8	177.5	177.4	178.4	179.0	179.1	179.8
Not Assigned	Power	Not Assigned	Production	250 QNW	166.5	166.8	167.5	168.3	168.5	168.5	168.4	168.0	168.1	167.1	166.4	166.1	165.0	167.1	165.9	164.7	164.5	165.2	165.0	165.8	165.3	164.5	164.2	164.4
Not Assigned	Power	Not Assigned	Sunday	200 QNW	181.8	180.5	179.2	177.0	154.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Not Assigned	Power	Not Assigned	Sunday	250 QNW	165.6	163.8	162.4	161.8	143.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Date	Day	Day Type																										
Jan-11-201	Thu	Excluded Days																										
Jan-12-201	Fri	Production																										
Jan-13-201	Sat	Production																										
Jan-14-201	Sun	Sunday																										
Jan-15-201	Mon	Monday																										
Jan-16-201	Tue	Production																										
Jan-17-201	Wed	Production																										
Jan-18-201	Thu	Production																										
Jan-19-201	Fri	Production																										
Jan-20-201	Sat	Production																										
Jan-21-201	Sun	Excluded Days																										
Jan-22-201	Mon	Excluded Days																										
Jan-23-201	Tue	Excluded Days																										

Enter LogTool Data Into AIRMaster

System Profiles [Close]

File Calculators Help

[Pencil] [Save] [Print] [Help] [Close]

Select
Facility [] Daytype Week Day System pressure control range 100.0 - 120.0 psig
System Production

Data Entry Profile Summary Totals

Cascade Order - click cell to toggle stage#/'off' [Copy Prev Col] [Graph]

Compressor	1	2	3	4	5	6	7	8	9	10
200 hp QNW	1	1	1	1	1	1	1	1	1	1
250 hp QNW	2	2	2	2	2	2	2	2	2	2
New 250 hp VSD	Off	Off	Off	Off	Off	Off	Off	Off	Off	Off





Profile data type: Power, kW [Paste From Clipboard] [Copy Prev Col] [Graph]

Compressor	Units	1	2	3	4	5	6	7	8	9	10
200 hp QNW	kW	178.1	178.3	177.9	177.1	177.7	178.1	178.0	177.9	177.7	17
250 hp QNW	kW	166.5	166.8	167.5	168.3	168.5	168.5	168.4	168.0	168.1	16
New 250 hp VSD	kW	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Enter LogTool Data Into AIRMaster

System Profiles X

File Calculators Help

    Close

Select

Facility Daytype System pressure control range

System

Data Entry Profile Summary Totals

Cascade Order - click cell to toggle stage#/'off' Copy Prev Col Graph

Compressor	1	2	3	4	5	6	7	8	9	10
200 hp QNW	1	1	1	1	1	1	1	1	1	1
250 hp QNW	2	2	2	2	2	2	2	2	2	2
New 250 hp VSD	Off	Off	Off	Off	Off	Off	Off	Off	Off	Off

Profile data type: Paste From Clipboard Copy Prev Col Graph

Compressor	Units	1	2	3	4	5	6	7	8	9	10
200 hp QNW	kW	181.8	180.5	179.2	177.0	154.2	0.0	0.0	0.0	0.0	
250 hp QNW	kW	165.6	163.8	162.4	161.8	143.1	0.0	0.0	0.0	0.0	
New 250 hp VSD	kW	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Enter LogTool Data Into AIRMaster

System Profiles

File Calculators Help

Select

Facility

System Production

Daytype Monday

System pressure control range 100.0 - 120.0 psig

Data Entry Profile Summary Totals

Cascade Order - click cell to toggle stage#/'off'

Copy Prev Col Graph

Compressor	1	2	3	4	5	6	7	8	9	10
200 hp QNw	1	1	1	1	1	1	1	1	1	1
250 hp QNw	2	2	2	2	2	2	2	2	2	2
New 250 hp VSD	Off	Off	Off	Off	Off	Off	Off	Off	Off	Off

Profile data type: Power, kW

Paste From Clipboard Copy Prev Col Graph

Compressor	Units	1	2	3	4	5	6	7	8	9	10
200 hp QNw	kW	0.0	0.0	0.0	0.0	84.6	175.9	177.1	181.6	182.2	18
250 hp QNw	kW	0.0	0.0	0.0	0.0	83.8	164.2	163.6	164.5	165.0	16
New 250 hp VSD	kW	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

The Baseline

System Profiles

File Calculators Help

Select

Facility Daytype System pressure control range 100.0 - 120.0 psig

System Production

Data Entry Profile Summary Totals

System Summary

Daytype	Total OpHrs	Avg Airflow, acfm	Avg Airflow, %Cs	Peak Demand, kW	Load Factor, %	Annual Energy, kWh	Annual Energy Cost, \$
Monday	1,040	1,459	38.4	348.8	51.3	349,102	23,564
Week Day	6,264	1,509	39.7	346.6	52.5	2,151,606	145,233
Sunday	260	1,434	37.7	347.4	51.0	86,809	5,860
System Totals	7,564	1,500	39.5	348.8	52.3	2,587,516	174,657

Copy To Clipboard

Total demand cost, \$ \$ 0

Total operating costs, \$ \$ 174,657

EEM's

Energy Efficiency Measures

File Calculators Help

Copy EEM Scenario Life Cycle Results Close

Facility: [Industrial Plant] EEM Scenario: leak reduction and add VSD

System: Production

Data Entry		Savings Summary			
Description		Include	Order	Edit/Review	Data Needs Review
DEMAND SIDE	Reduce Air Leaks	<input checked="" type="checkbox"/>	1	...	<input type="checkbox"/>
	Improve End Use Efficiency	<input type="checkbox"/>		...	<input type="checkbox"/>
	Reduce System Air Pressure	<input type="checkbox"/>		...	<input type="checkbox"/>
SUPPLY SIDE	Use Unloading Controls	<input type="checkbox"/>		...	<input type="checkbox"/>
	Adjust Cascading Set Points	<input type="checkbox"/>		...	<input type="checkbox"/>
	Use Automatic Sequencer	<input type="checkbox"/>		...	<input type="checkbox"/>
	Reduce Run Time	<input checked="" type="checkbox"/>	2	...	<input checked="" type="checkbox"/>
	Add Primary Receiver Volume*	<input type="checkbox"/>		...	<input type="checkbox"/>

* Available only if air storage capacity was entered in the system module. Visit the system module to edit this value.
Only lubricant-injected rotary screw compressors with unloading controls will benefit from adding receiver volume.

EEM's

EEM - Reduce Air Leaks

File Calculators Help

Results Close

Facility System

Description Measure cost, \$

Measured data

Compressor Operations To Feed Leaks

Compressor	Units	Airflow, acfm
200 hp QNW	acfm	0
250 hp QNW	acfm	200
New 250 hp VSD	acfm	0

Maximum hourly system airflow, acfm (according to entered profile values)

Leak Airflow Values

Peak system requirement + leaks	Airflow, acfm <input type="text" value="1514"/>	% Cs. <input type="text" value="39.8"/>
Leaks	<input type="text" value="200"/>	<input type="text" value="5.3"/>
Peak system requirement	<input type="text" value="1314"/>	<input type="text" value="34.6"/>

Reduce leaks by acfm %

EEM's

EEM - Reduce Run Time

File Calculators Help

Results Close

Facility

System Production

Data View

Existing

Proposed

Measure Description

Description Reduce Run Time Measure cost, \$ 106700

Proposed Run Time Data

Daytype Monday

A check indicates a compressor is available or online. Uncheck to force a compressor off.

Compressor	Airflow Cap., acfm	1	2	3	4	5	6	7	8	9
200 hp QNw	1,006	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
250 hp QNw	1,266	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
New 250 hp VSD	1,527	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Available Airflow, acfm		1527	1527	1527	1527	1527	1527	1527	1527	1527
Required Airflow, acfm		0	0	0	0	220	1314	1314	1314	1314

VSD Performance Graph

EEM's

Energy Efficiency Measures

File Calculators Help

Copy EEM Scenario Life Cycle Results Close

Facility: International Paper
System: Production
EEM Scenario: leak reduction and add VSD


Data Entry Savings Summary

Description	Energy Savings, kWh	Energy Savings, \$	Energy Savings, %	Demand Savings, kW	Demand Savings, \$	Installed Cost, \$	Total Savings, \$	Simple Payback, years
Reduce Air Leaks	457,487	30,880	17.7	64.1	0	5,000	30,880	0.2
Reduce Run Time	484,848	32,727	18.7	64.9	0	106,700	32,727	3.3
TOTALS	942,335	63,608	36.4	129.0	0	111,700	63,608	1.8


Double-click row to view corresponding measure input data

Copy To Clipboard

Bar Graphs



Bar Graphs



Calculators

SCFM - ACFM Conversion Calculator

Actual Conditions

Elevation, ft.

Atmospheric pressure, psia

Ambient temperature, °F

Relative humidity, %

Standard Conditions Method

ASME CAGI/ISO Pneuop

psia

°F

%

Results

Required airflow acfm ← scfm

(Enter: acfm to calculate scfm OR scfm to calculate acfm)

Calculators

Air Storage Capacity Calculator [X]

Measured Test Conditions

Elevation, ft.

Atmospheric pressure, psia

Compressor capacity, acfm

Full load or cut-in pressure, psig


Unload or cut-out pressure, psig

Pump-up time, sec.

Drain-down time, sec.

Results

Air storage capacity (receivers + distribution pipe), ft³

 U.S. Department of Energy
Energy Efficiency and Renewable Energy
Bringing you a responsible tomorrow energy is clean, abundant, reliable, and affordable

Cycle Time Calculator [X]

Actual Conditions

Elevation, ft.

Atmospheric pressure, psia

Compressor capacity, acfm

System airflow requirement, acfm

System volume, cubic feet

Full load or cut-in pressure, psig

Unload or cut-out pressure, psig


Results

Pump-up time, sec.

Drain-down time, sec.

Total cycle time, sec.

Performance Profile Graph



VSD Performance Graph



Another Airmaster+ Example Profile Data

System Profiles

File Calculators Help

Select

Facility Daytype Production System pressure control range 107.0 - 118.9 psig

System Production

Data Entry Profile Summary Totals

Cascade Order - click cell to toggle stage#/'off'

Compressor	1	2	3	4	5	6	7	8	9	10
AC7400	1	1	1	1	1	1	1	1	1	1
AC7401	2	2	2	2	2	2	2	2	2	2
AC7402	3	3	3	3	3	3	3	3	3	3
ZR 132 VSD	Off	Off	Off	Off	Off	Off	Off	Off	Off	Off

Copy Prev Col Graph

Profile data type: Power, kW

Compressor	Units	1	2	3	4	5	6	7	8	9	10
AC7400	kW	31.3	31.1	31.2	31.1	31.1	31.3	31.2	31.3	31.5	3
AC7401	kW	33.8	33.3	34.9	34.7	34.7	34.9	34.2	34.3	34.8	3
AC7402	kW	105.9	106.0	104.6	104.1	104.6	106.4	107.0	107.0	104.9	10
ZR 132 VSD	kW	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Paste From Clipboard Copy Prev Col Graph

Where did this data come from?

Another Airmaster+ Example Day Type From Log Tool

The screenshot shows the LogTool v2 interface. At the top, there are menu options: File, Tools, Help. Below that, there are buttons for "Open an Existing Database (.MDB File)", "Create a New Database (.MDB File)", and "Help". The "File" field contains "Boehringer Full Data LogTool.mdb" and the "Folder" field contains "D:\Audit Related\Boehringer Ingelheim". There is an "Import Logger Data" button and three view mode buttons: "Trend", "Scatter", and "DayType".

The main data table is titled "Logger Data in: Boehringer Full Data LogTool.mdb". It has columns for View, Trend, Scatter, DayType, Name, Type, Units, Period, System, Start, End, and Interval (sec.). The "DayType" column has a sub-column "Include" with checkboxes. The rows for "AC7400", "AC7401", and "AC7402" are highlighted in yellow, and their "Include" checkboxes are checked. A red box highlights the "DayType" column headers. A blue callout bubble points to the "DayType" button with the text: "Select the compressors that are online and click the Day Type Button".

View	Trend		Scatter		DayType	Name	Type	Units	Period	System	Start	End	Interval (sec.)
	Y1	Y2	X	Y	Include								
Data	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	100 psi regulator	Pressure	psig	Baseline	Not Assignec	6/28/2021 11:45:07	7/14/2021 15:35:59	4
Data	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	AC7400	Power	kW	Baseline	Not Assignec	6/28/2021 12:04:21	7/14/2021 15:55:13	4
Data	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	AC7401	Power	kW	Baseline	Not Assignec	6/28/2021 12:37:45	7/14/2021 16:28:37	4
Data	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	AC7402	Power	kW	Baseline	Not Assignec	6/28/2021 13:04:29	7/14/2021 16:55:21	4
Data	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Bio Reactor 1330	Pressure	psig	Baseline	Not Assignec	6/29/2021 09:31:22	7/15/2021 13:22:14	4
Data	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Bio Reactor 1730	Pressure	psig	Baseline	Not Assignec	6/29/2021 09:27:22	7/15/2021 13:18:14	4
Data	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Dry Tank	Pressure	psig	Baseline	Not Assignec	6/28/2021 11:35:29	7/14/2021 15:26:21	4
Data	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	PI 1390 Top Floor	Pressure	psig	Baseline	Not Assignec	6/29/2021 09:35:19	7/15/2021 13:26:11	4
Data	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Wet Tank	Pressure	psig	Baseline	Not Assignec	6/28/2021 12:00:32	7/14/2021 15:51:24	4


Select the compressors that are online and click the Day Type Button

Another Airmaster+ Example

System	Type	Period	DayTypeName	ChannelName	Hr_01	Hr_02	Hr_03	Hr_04	Hr_05	Hr_06	Hr_07	Hr_08	Hr_09	Hr_10	Hr_11	Hr_12	Hr_13	Hr_14	Hr_15	Hr_16	Hr_17	Hr_18	Hr_19	Hr_20	Hr_21	Hr_22	Hr_23	Hr_24
Not Assign	Power	Baseline	Production	AC7400	31.3	31.1	31.2	31.1	31.1	31.3	31.2	31.3	31.5	31.7	31.4	31.1	30.6	31.3	30.9	30.8	31.6	32.4	31.6	31.2	30.9	31.1	31.3	31.7
Not Assign	Power	Baseline	Production	AC7401	33.8	33.3	34.9	34.7	34.7	34.9	34.2	34.3	34.8	34.1	33.9	34.5	33.4	34.0	34.0	34.5	34.0	33.5	32.7	34.1	33.7	34.0	35.0	34.6
Not Assign	Power	Baseline	Production	AC7402	105.9	106.0	104.6	104.1	104.6	106.4	107.0	107.0	104.9	107.7	107.7	107.1	107.1	106.4	106.2	105.1	107.1	108.6	107.5	105.9	105.0	104.9	104.3	106.8

Date	Day	Day Type
Jun-28-20	Mon	Production
Jun-29-20	Tue	Production
Jun-30-20	Wed	Production
Jul-01-202	Thu	Production
Jul-02-202	Fri	Production
Jul-03-202	Sat	Production
Jul-04-202	Sun	Production
Jul-05-202	Mon	Production
Jul-06-202	Tue	Production
Jul-07-202	Wed	Production
Jul-08-202	Thu	Production
Jul-09-202	Fri	Production
Jul-10-202	Sat	Production
Jul-11-202	Sun	Production
Jul-12-202	Mon	Production
Jul-13-202	Tue	Production
Jul-14-202	Wed	Production

System: Not Assigned, Period: Baseline



Another Airmaster+ Example

The screenshot shows the 'System Profiles' software window. The 'Profile Summary' tab is active, displaying a 'System Summary' table. The table has the following columns: Daytype, Total OpHrs, Avg Airflow, acfm, Avg Airflow, %Cs, Peak Demand, kW, Load Factor, %, Annual Energy, kWh, and Annual Energy Cost, \$. The data for the 'Production' daytype is as follows:

Daytype	Total OpHrs	Avg Airflow, acfm	Avg Airflow, %Cs	Peak Demand, kW	Load Factor, %	Annual Energy, kWh	Annual Energy Cost, \$
Production	8,760	490	19.1	174.5	33.2	1,503,143	150,314
System Totals	8,760	490	19.1	174.5	33.2	1,503,143	150,314

Below the table, the software shows 'Total demand cost, \$' as \$0 and 'Total operating costs, \$' as \$150,314.

Compressed Air Baseline Energy using \$0.10/kWh							
Daytype	Total OpHrs	Avg Airflow, acfm	Avg Airflow, %Cs	Peak Demand, kW	Load Factor, %	Annual Energy, kWh	Annual Energy Cost, \$
Production	8,760	490	19.1	174.5	33.2	1,503,143	\$150,314
System Totals	8,760	490	19.1	174.50	33.2	1,503,143	\$150,314

Another Airmaster+ Example

Energy Efficiency Measures

File Calculators Help

Copy EEM Scenario Life Cycle Results Close

Facility [] EEM Scenario EEM 2

System Production

Data Entry Savings Summary

Description	Energy Savings, kWh	Energy Savings, \$	Energy Savings, %	Demand Savings, kW	Demand Savings, \$	Installed Cost, \$	Total Savings, \$	Simple Payback, years
Use Automatic Sequencer	570,410	57,041	37.9	65.3	0	32,600	57,041	0.6
Add AD 400 dryer	104,541	10,454	7.0	11.9	0	26,351	10,454	2.5
TOTALS	674,950	67,495	44.9	77.2	0	58,951	67,495	0.9


Double-click row to view corresponding measure input data

Copy To Clipboard

EEM -- Sequence Compressors purchase AD400 dryer							
Description	Energy Savings, kWh	Energy Savings, \$	Energy Savings, %	Demand Savings, kW	Installed Cost, \$	Total Savings, \$	Simple Payback, years
Use Automatic Sequencer	570,410	\$57,041.00	37.9	65.3	\$32,600.00	\$57,041.00	0.6
Add AD 400 dryer	104,541	\$10,454.00	7	11.9	\$26,351.00	\$10,454.00	2.5
TOTALS	674,950	\$67,495.00	44.9	77.2	\$58,951.00	\$67,495.00	0.9


LogTool Scatter Plot

Wet Tank (Pressure) vs. AC7400 (Power)
4 second interval data for System (Not Assigned) and Period (Baseline)
Y-Axis time shifted by 1 seconds.




LogTool Scatter Plot

Wet Tank (Pressure) vs. AC7401 (Power)
4 second interval data for System (Not Assigned) and Period (Baseline)
Y-Axis time shifted by 1 seconds.



LogTool Scatter Plot

Wet Tank (Pressure) vs. AC7402 (Power)
4 second interval data for System (Not Assigned) and Period (Baseline)
Y-Axis time shifted by 1 seconds.



MEASUR Tool

MEASUR

U.S. DEPARTMENT OF ENERGY
Energy Efficiency & Renewable Energy

Add New ▾

Home

- All Assessments
- New Assessment
- Examples
 - Reheat Furnace Case Study
 - Basic Pump Example
 - Fan Example
 - 3 Header Example
 - Treasure Hunt Example

Data Exploration

All Calculators

- General
- Compressed Air
- Fans
- Lighting
- Motors
- Process Cooling
- Process Heating
- Pumps
- Steam
- Waste Water

Settings

- Custom Materials
- Tutorials
- About
- Feedback
- Acknowledgments
- Translate

v0.9.2-beta ⓘ

Welcome to the most efficient way to manage and optimize your facilities' systems and equipment.

Create an assessment to model your system and find opportunities for efficiency or run calculations from one of our many property and equipment calculators. Get started with one of the following options.

Create Assessment
Model a system and explore multiple optimization scenarios.

- Create Pump Assessment**
formerly DOE Pumping System Assessment Tool (PSAT)
- Create Process Heating Assessment**
formerly DOE Process Heating Assessment and Survey Tool (PHAST)
- Create Fan Assessment**
formerly DOE Fan System Assessment Tool (FSAT)
- Create Steam Assessment**
formerly DOE Steam System Modeler Tool (SSMT)
- Create Treasure Hunt**
Energy efficiency calculators for facilitating a Treasure Hunt
- Create Waste Water Assessment**
Based on the Bio-Tiger Model for Wastewater Treatment Plants

[View All Your Assessments](#)

Properties & Equipment Calculators
Generate detailed properties and test a variety of adjustments.

- General
- Compressed Air
- Fans
- Lighting
- Motors
- Process Cooling
- Process Heating
- Pumps
- Steam
- Waste Water

Inventory Management
Create and manage equipment inventory.

- Create Motor Inventory**
based on DOE's MotorMaster+ tool
- Create Data Exploration**
based on DOE's LogTool

MEASUR Tool

Compressed Air Calculators



Compressed Air Reduction

This calculator is used to quantify the energy savings associated with reducing compressed air usage.



Compressed Air Pressure Reduction

This calculator is used to quantify the energy savings associated with reducing compressed air system pressure.




Actual to Standard Airflow

The calculator converts ACFM (Actual cubic feet per minute) to SCFM (Standard cubic feet per minute) and vice versa for the given conditions using either ASME standard conditions or CAGI/ISO standard conditions.



Leak Loss Estimator - Bag Method

Estimates the leakage losses in a compressed air system using the bag method



Pneumatic Air Requirement

Estimate the quantity of air required by a specific single acting or a double acting piston cylinder compressor



Compressed Air - Leak Survey

Used to quantify the energy savings associated with reducing compressed air leaks.

MEASUR Tool



Receiver Tank Sizing

Calculate the required size of the receiver tank



Usable Air Capacity

Estimate the quantity of compressed air that is available for use




Pipe Sizing

Determine pipe diameter when the volumetric flow velocity, pressure, and design velocity are known



Velocity in the Piping

Estimate the velocity of compressed air throughout system piping



System Capacity

Determine total capacity of compressed air system or specific pipes and receiver tanks



Operation Costs

Estimate the cost of operation of the compressor in both fully and partially loaded instances

Let's compare to old Log Tool

Data Exploration Setup Day Type Analysis Visualization

1 Import Data **2 Select Header Row** 3 Refine Data 4 Map Date and Time

Select a header row and advance to the next file

Apply my selections for all datasets

International_Paper_Co_inside_200hp_QSI1.csv

International_Paper_Co_outside_QSI_n250h.csv

Select Header Row

<input type="radio"/>	Plot Title: International Paper Co inside 200hp QSI1		
<input checked="" type="radio"/>	#	Date Time, GMT-07:00	200hp QSI1000, kW
<input type="radio"/>	1	01/11/18 11:35:38 AM	179.256
<input type="radio"/>	2	01/11/18 11:35:41 AM	179.159
<input type="radio"/>	3	01/11/18 11:35:44 AM	179.061
<input type="radio"/>	4	01/11/18 11:35:47 AM	178.964
<input type="radio"/>	5	01/11/18 11:35:50 AM	179.159
<input type="radio"/>	6	01/11/18 11:35:53 AM	179.256
<input type="radio"/>	7	01/11/18 11:35:56 AM	179.451
<input type="radio"/>	8	01/11/18 11:35:59 AM	179.354
<input type="radio"/>	9	01/11/18 11:36:02 AM	179.451

Back

Next

Let's compare to old Log Tool

Data Exploration Setup Day Type Analysis Visualization

1 Import Data 2 Select Header Row 3 **Refine Data** 4 Map Date and Time

Mark the columns to be used for analysis and advance to the next file

Apply my selections for all datasets

International_Paper_Co_inside_200hp_QSI1.csv International_Paper_Co_outside_QSI_n250h.csv

Column Name	Use Column	Alias	Display Unit
#	<input type="checkbox"/>	#	+Add
Date Time, GMT-07:00	<input checked="" type="checkbox"/>	Date Time, GMT-07:00	+Add
200hp QSI1000, kW	<input checked="" type="checkbox"/>	200hp QSI1000, kW	+Add

Original Data

#	Date Time, GMT-07:00	200hp QSI1000, kW
1	01/11/18 11:35:38 AM	179.256
2	01/11/18 11:35:41 AM	179.159

Let's compare to old Log Tool

Data Exploration Setup Day Type Analysis Visualization

1 Import Data 2 Select Header Row 3 Refine Data 4 **Map Date and Time**

- Timestamps are required for Day Type Analysis and time series data visualizations. Advance ahead if you won't be working with time data.
 - Mark "Includes Date" if the column contains a date and time or a date only
 - Mark "Includes Time Only" if the column contains a time only

> Timestamp Help

Apply my selections for all datasets

International_Paper_Co_inside_200hp_QSI1.csv International_Paper_Co_outside_QSI_n250n.csv

Column Name	Includes Date	Includes Time Only ?
Date Time, GMT-07:00	<input checked="" type="checkbox"/>	<input type="checkbox"/>
outside 250 hp, kW	<input type="checkbox"/>	<input type="checkbox"/>

Data Collection Interval

Back Finish Setup

Let's compare to old Log Tool

Data Exploration Setup **Day Type Analysis** Visualization

Graph Data Table Data: Total Aggregated Equipment Data Day Types Days Apply To Assessment

Total Aggregated Equipment Data (Hourly Data Average)

Day Types: Weekday Weekend Excluded +Add New Reset

January 2018

Su	Mo	Tu	We	Th	Fr	Sa
	1	2	3	4	5	6
7	8	9	10	11	12	13
14	15	16	17	18	19	20
21	22	23	24	25	26	27
28	29	30	31			

Day Type Average Interval: Hourly

Update Analysis

Select Columns for Total Aggregated Equipment Data:

Apply my selections for all datasets

Column Name	Include in Aggregated Data
International_Paper_Co_inside_200hp_QSI1.csv	<input type="checkbox"/>
International_Paper_Co_outside_QSI_n250h.csv	<input type="checkbox"/>
200hp QSI1000, kW	<input checked="" type="checkbox"/>

Enter LogTool Data Into AIRMaster

Let's compare to old Log Tool

Data Exploration
Setup **Day Type Analysis** Visualization
🔒 ⬇️ 📄 🏠

Graph **Data Table** Data: Total Aggregated Equipment Data

Display Selected
Display All
Day Types
Days
Apply To Assessment

Day Type Summaries (Total Aggregated Equipment Data)

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23
Weekday	228.377	228.905	228.787	242.79	286.037	316.346	332.26	346.52	346.149	345.545	344.301	343.832	342.328	332.301	340.319	340.034	339.788	340.325	342.196	342.645	343.561	343.737	343.301	343.897
Weekend	344.453	337.26	294.106	242.105	230.29	142.398	141.889	141.907	142.721	142.478	142.019	141.54	140.985	140.712	140.507	139.788	139.802	140.537	141.008	141.615	141.356	140.843	141.28	141.524
Excluded	343.151	344.6	343.84	343.205	343.652	343.678	345.983	345.427	344.92	343.188	342.499	343.677	341.853	340.265	338.766	343.887	344.11	343.776	347.291	347.341	349.506	349.346	349.406	350.719

Copy Table

Day Summaries (Total Aggregated Equipment Data)

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23
Weekday																								
Jan 12, 2018	350.503	350.457	349.767	350.922	349.444	350.735	350.126	349.697	348.726	347.911	348.143	348.613	346.908	343.422	343.798	343.359	343.994	344.688	346.835	347.03	350.133	349.088	350.24	350.696
Jan 15, 2018	-62.48	-62.481	-62.479	-62.48	135.607	340.068	340.692	346.157	347.243	347.519	348.732	347.609	345.048	343.513	341.95	341.139	340.554	341.815	343.719	344.359	345.83	346.652	346.369	346.135
Jan 16, 2018	347.61	347.97	347.122	346.248	347.541	347.869	347.655	346.948	347.811	345.907	343.795	343.826	342.966	340.637	341.396	342.32	341.424	341.937	343.92	343.374	343.997	345.062	343.421	344.827
Jan 17, 2018	344.128	344.633	344.586	346.258	346.296	347.187	345.95	346.432	344.017	345.032	342.959	343.33	341.718	340.763	341.098	341.488	341.749	342.284	344.047	344.131	344.641	344.578	344.717	345.682
Jan 18, 2018	344.129	344.662	345.205	345.692	346.339	346.123	346.506	345.632	345.089	344.363	341.707	339.446	338.237	279.357	336.221	335.939	335.253	335.215	337.038	338.875	338.816	338.304	338.122	337.499
Jan 19, 2018	337.229	339.573	339.789	338.727	339.595	339.627	341.793	339.637	339.3	338.219	336.391	336.754	336.199	334.947	336.405	335.468	334.589	335.592	337.082	337.984	338.112	338.727	336.751	339.25
Jan 22, 2018	-62.479	-62.48	-62.48	36.16	137.439	142.81	253.096	351.139	350.856	349.867	348.384	347.243	345.219	343.466	341.363	340.524	340.952	340.747	342.73	342.761	343.397	343.746	343.488	343.188
Weekend																								
Jan 13, 2018	351.026	349.585	351.782	351.001	351.894	352.74	351.297	351.961	352.383	352.372	349.311	346.937	345.905	345.548	344.381	343.145	343.407	344.375	346.107	344.937	346.216	345.54	345.22	346.343
Jan 14, 2018	347.315	344.282	341.634	338.817	289.6	-62.48	-62.481	-62.479	-62.48	-62.48	-62.482	-62.481	-62.48	-62.48	-62.48	-62.488	-62.483	-62.48	-62.48	-62.479	-62.479	-62.48	-62.48	-62.48
Jan 20, 2018	337.969	338.586	339.17	341.079	342.147	341.811	341.216	340.627	343.462	342.497	343.729	344.185	342.992	342.259	342.607	340.974	340.766	342.729	342.885	346.484	344.162	342.792	344.86	344.712
Jan 21, 2018	341.5	316.585	143.837	-62.476	-62.479	-62.478	-62.478	-62.48	-62.48	-62.478	-62.48	-62.48	-62.477	-62.479	-62.481	-62.48	-62.481	-62.478	-62.479	-62.48	-62.476	-62.48	-62.479	-62.48
Excluded																								
Jan 11, 2018												346.218	345.07	343.465	342.276	343.887	344.11	343.776	347.291	347.341	349.506	349.346	349.406	350.719
Jan 23, 2018	343.151	344.6	343.84	343.205	343.652	343.678	345.983	345.427	344.92	343.188	342.499	341.135	338.636	337.064	335.257									

Copy Table

Day Types: ✖ Weekday ✖ Weekend Excluded +Add New Reset

January 2018

Day Type Average Interval: Hourly

Update Analysis

Select Columns for Total Aggregated Equipment Data:

SELECT POTENTIAL ADJUSTMENT PROJECTS

Select potential adjustment projects to explore opportunities to increase efficiency and the effectiveness of your system.

Add New Scenario

Modification Name

Reduce Run Time | Supply 1

Implementation Cost \$

Day Type

	Capacity acfm	Shutdown Timer	0:00	1:00	2:00	3:00	4:00	5:00	6:00	7:00	8:00	9:00	10:00	11:00	12:00
200 hp QNW	933 acfm	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
250 hp QNW	1261 acfm	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
New Compressor	1141 acfm	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Available Airflow			933	933	933	933	933	2,074	2,074	2,074	2,074	2,074	2,074	2,074	2,074
Required Airflow			705	708	709	775	907	1,085	1,347	1,526	1,527	1,524	1,524	1,521	1,513
Power, kW			159.5	159.7	159.8	164.1	172.7	244.1	300.9	357.7	357.8	357.6	357.6	357.4	344.2

Reduce Air Leaks | Demand 2

Implementation Cost \$

Leak Flow acfm

Leak Reduction %

Improve End Use Efficiency | Demand Off

Reduce System Air Pressure | Supply Off

Add Primary Receiver Volume | Supply Off

MODIFICATION RESULTS

All Day Types

	Baseline	VSD
Percent Savings (%)	---	39.6%
Flow Reallocation Energy Savings	---	391,627 kWh
Reduce Air Leaks Energy Savings	---	585,745 kWh
Reduce Run Time Energy Savings	---	-233,967 kWh
Peak Demand	346.6 kW	273.86 kW
Annual Energy	2,620,045 kWh	1,876,639 kWh
Annual Emission Output Rate	1,050,821 tonne CO ₂	752,664 tonne CO ₂
Peak Demand Savings	---	72.74 kW
Annual Energy Savings	---	743,405 kWh
Annual Emission Savings	---	298,158 tonne CO ₂
Flow Reallocation Savings	---	\$25,847.38
Reduce Air Leaks Savings	---	\$55,352.94
Reduce Run Time Savings	---	-\$22,109.88
Peak Demand Cost	\$0.00	\$0.00
Annual Energy Cost	\$247,594.21	\$177,342.40
Annual Cost	\$247,594.21	\$177,342.40
Peak Demand Cost Savings	---	\$0.00
Annual Energy Cost Savings	---	\$70,251.80
Annual Cost Savings	---	\$70,251.80

Next Week Session 4 – Air Treatment

- Compressed air must be dried. This is an undeniable statement of fact.
 - Today's modern industry can no longer tolerate the problems of wet, dirty compressed air.
 - Wet air causes rust, pitting, blockages, and freeze-ups, with resultant component failure and product rejection.
 - Wet air is a major contributor of downtime, causing millions of dollars of lost production.

Homework for Week 3 – Compressor Controls

- Explain each of the following control methods:
 - Start/Stop
 - Load/Unload
 - Modulating
 - Variable Displacement
 - Variable Speed
 - Sequencer
 - Master Compressor Controller?
 - Pressure Flow Control?

Questions?